

Radio link outdoor LCHD-Uniboot/LCHD-Uniboot cable assembly ultra low loss MM50/125 OM3

RL - FO Cable Assembly 2 x 50/125 OM3, LCHD Uniboot/LCHD Uniboot, type S, FRPU, ULL



SPECIFICATION	
Cable design	Round dielectric cable
Cable Outer Diameter, mm	4,8 mm
Fiber type	MM 50/125 OM3
Connector, Side A	LCHD Uniboot Duplex
Connector, Side B	LCHD Uniboot Duplex
Polarity	Type S (straight, A-B/B-A)
Loss Category	MM, Ultra Low Loss
Fire safety	IEC 60332-1

Part Numbers	
81113108	RL - FO Cable Assembly 2 x 50/125 OM3, LCHD Uniboot/LCHD Uniboot, type S, FRPU, ULL, 2 m
81113109	RL - FO Cable Assembly 2 x 50/125 OM3, LCHD Uniboot/LCHD Uniboot, type S, FRPU, ULL, 5 m
81113110	RL - FO Cable Assembly 2 x 50/125 OM3, LCHD Uniboot/LCHD Uniboot, type S, FRPU, ULL, 10 m
81113101	RL - FO Cable Assembly 2 x 50/125 OM3, LCHD Uniboot/LCHD Uniboot, type S, FRPU, ULL, 25 m
81113102	RL - FO Cable Assembly 2 x 50/125 OM3, LCHD Uniboot/LCHD Uniboot, type S, FRPU, ULL, 30 m
81113103	RL - FO Cable Assembly 2 x 50/125 OM3, LCHD Uniboot/LCHD Uniboot, type S, FRPU, ULL, 50 m
81113104	RL - FO Cable Assembly 2 x 50/125 OM3, LCHD Uniboot/LCHD Uniboot, type S, FRPU, ULL, 70 m
81113105	RL - FO Cable Assembly 2 x 50/125 OM3, LCHD Uniboot/LCHD Uniboot, type S, FRPU, ULL, 100 m
81113106	RL - FO Cable Assembly 2 x 50/125 OM3, LCHD Uniboot/LCHD Uniboot, type S, FRPU, ULL, 150 m
81113107	RL - FO Cable Assembly 2 x 50/125 OM3, LCHD Uniboot/LCHD Uniboot, type S, FRPU, ULL, 200 m