

Radio Link outdoor LC-Uniboot switchable/LC-Duplex cable assembly SM9/125 OS2

RL - FO Cable Assembly 2 x 09/125 OS2, LC Uniboot/LC duplex, type S, FRPU



| SPECIFICATION            |                              |
|--------------------------|------------------------------|
| Fiber quantity           | 2 fibers                     |
| Cable design             | Round dielectric cable       |
| Cable Outer Diameter, mm | 4,8 mm                       |
| Fiber type               | SM 9/125 OS2                 |
| Connector, Side A        | LC Duplex Uniboot switchable |
| Connector, Side B        | LC Duplex                    |
| Polarity                 | Type S (straight, A-B/B-A)   |
| Loss Category            | SM, Standard Loss            |
| Fire safety              | IEC 60332-1                  |

| Part Numbers |                                                                                  |
|--------------|----------------------------------------------------------------------------------|
| 81109001     | RL - FO Cable Assembly 2 x 09/125 OS2, LC Uniboot/LC duplex, type S, FRPU, 30 m  |
| 81109002     | RL - FO Cable Assembly 2 x 09/125 OS2, LC Uniboot/LC duplex, type S, FRPU, 50 m  |
| 81109003     | RL - FO Cable Assembly 2 x 09/125 OS2, LC Uniboot/LC duplex, type S, FRPU, 70 m  |
| 81109004     | RL - FO Cable Assembly 2 x 09/125 OS2, LC Uniboot/LC duplex, type S, FRPU, 100 m |
| 81109005     | RL - FO Cable Assembly 2 x 09/125 OS2, LC Uniboot/LC duplex, type S, FRPU, 150 m |