

Radio link outdoor LCHD-Uniboot/LC-Duplex cable assembly ultra low loss MM50/125 OM2

RL - FO Cable Assembly 2 x 50/125 OM2, LCHD Uniboot/LC duplex, type S, FRPU, ULL



SPECIFICATION

Cable design	Round dielectric cable
Cable Outer Diameter, mm	4,8 mm
Fiber type	MM 50/125 OM2
Connector, Side A	LCHD Uniboot Duplex
Connector, Side B	LC Duplex
Polarity	Type S (straight, A-B/B-A)
Loss Category	MM, Ultra Low Loss

Part Numbers

81112101	RL - FO Cable Assembly 2 x 50/125 OM2, LCHD Uniboot/LC duplex, type S, FRPU, ULL, 2 m
81112102	RL - FO Cable Assembly 2 x 50/125 OM2, LCHD Uniboot/LC duplex, type S, FRPU, ULL, 5 m
81112103	RL - FO Cable Assembly 2 x 50/125 OM2, LCHD Uniboot/LC duplex, type S, FRPU, ULL, 10 m
81112104	RL - FO Cable Assembly 2 x 50/125 OM2, LCHD Uniboot/LC duplex, type S, FRPU, ULL, 25 m
81112105	RL - FO Cable Assembly 2 x 50/125 OM2, LCHD Uniboot/LC duplex, type S, FRPU, ULL, 30 m
81112106	RL - FO Cable Assembly 2 x 50/125 OM2, LCHD Uniboot/LC duplex, type S, FRPU, ULL, 50 m
81112107	RL - FO Cable Assembly 2 x 50/125 OM2, LCHD Uniboot/LC duplex, type S, FRPU, ULL, 70 m
81112108	RL - FO Cable Assembly 2 x 50/125 OM2, LCHD Uniboot/LC duplex, type S, FRPU, ULL, 100 m
81112109	RL - FO Cable Assembly 2 x 50/125 OM2, LCHD Uniboot/LC duplex, type S, FRPU, ULL, 150 m
81112110	RL - FO Cable Assembly 2 x 50/125 OM2, LCHD Uniboot/LC duplex, type S, FRPU, ULL, 200 m